

### VNBP AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designation RWY NR	TRUE & MAG BRG	Dimensions of RWY (M)	Strength(PCN) and surface of RWY and SWY	THR Coordinates	THR elevation and Highest elevation of TDZ of Precision APP RWY
1	2	3	4	5	6
15	151°	1200x 30	Bitumen	274021N * 0842552E	205m AMSL
33	331°	1200x30	Bitumen	274054N * 0842532 E	207m AMSL
Slope of RWY-SWY	SWY Dimensions (M)	CWY Dimensions (M)	Strip Dimensions (M)	OFZ	Remarks
7	8	9	10	11	12
.....	.....	.....	.....	.....	.....

### VNBP AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
15	1200	1200	1200	1200	
33	1200	1200	1200	1200	

### VNBP AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	THR LGT color WBAR	VASIS PAPI	TDZ LGT LEN	RWY Center Line LGT Length, spacing color, INTST	RWY edge LGT LEN, spacing color INTST	RWY End LGT color	SWY LGT LEN (M) color	Remarks
15	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	
33	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	

### VNBP AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1.	ABN Location, characteristics and hours of operation	ABN : at Tower Building.
2.	LDI Location and LGT Anemometer Location and LGT	LDI: Anemometer:
3.	TWY edge and Centre line lighting	Edge: NIL Centre Line : NIL
4.	Secondary power supply / switch over time	Available.
5.	Remarks	

\* WGS 84 Coordinates