

GEN 2.2 ABBREVIATIONS USED IN AIS PUBLICATION

Abbreviations marked by an asterisk (*) are either different from or not contained in ICAO Doc 8400.

	A	BTN	Between
ATIS	Automatic terminal information service		
ATM	Air traffic management	C	C Degrees Celsius (Centigrade)
ATN	Aeronautical telecommunication network	CAA*	Civil Aviation Authority
ATS	Air traffic services	CAAN*	Civil Aviation Authority of Nepal
ATTN	Attention	CAT	Category or clear air turbulence
ATZ	Aerodrome traffic zone	CAVOK	(to be pronounced "KAV-OH-KAY)" Visibility, cloud and present weather better than prescribed values or conditions
AUG	August		
AUTH	Authorised or Authorisation	CB, cc	Cumulonimbus, cirrocumulus
AUW	All up weight	CDN	Coordination (message type designator)
AUX	Auxiliary	CFM*	Confirm or I confirm
AVASIS	Abbreviated visual 'approach slope indicator system	CH	Channel
AVBL	Available or availability	CHG*	Change or changed
AVG	Average	CHG	Modification (Message)
AVGAS	Aviation gasoline	CIP	Commercial important person
AWY	Airway	CIV	Civil
AZM	Azimuth	CK	Check
	B	CL*	Centre - line
B	Blue	CLBR	Calibration
BA	Braking Action	CLD	Cloud
BCN	Beacon (Aeronautical ground light)	CLG	Calling
BCST	Broadcast	CLR	Clears) or cleared to or clearance
BDRY	Boundary	CLSD	Close or closed or closing
BECMG	Becoming	CM	Centimeter
BFR	Before	CMB	Climber, climbing
BKN	Broken	CMPL	Completion or completed or complete
BLDG	Building	CNL	Cancel or cancelled or flight plan cancellation
BLW	Below	CNS	Communications navigations and surveillance
BOMB	Bombing	COM	Communication
BR	Mist	CONC	Concrete
BRF	Short (used to indicate the type of approach desired or required)	COND	Condition
BRG	Bearing		
BRKG	Braking		
BS	Commercial broadcasting station		