

Table-1*

Airspace Class	C	G	
		ABOVE 900 M (3000 ft) AMSL or above 300 M (1000 ft) above terrain, whichever is the higher	At and below 900 m (3000 ft) AMSL or 300 m (1000 ft) above terrain, whichever is the higher
Distance from cloud	1500 m horizontally 300 m (1000 ft) vertically	1500 m horizontally 300 m (1000 ft) vertically	Clear of cloud and in sight of the surface
Flight Visibility	8 km at and above 3050 m (10000 ft) AMSL, 5 Km below 3050 m (10000 ft) AMSL	8 km at and above 3050 m (10000 ft) AMSL, 5 Km below 3050 m (10000 ft) AMSL	5 km*
<p>* HELICOPTERS may be permitted at 1500 M flight visibility, if maneuvered at a speed that will give adequate opportunity to observe other traffic or any obstacles in time to avoid collision.</p>			

6. VFR flights shall comply with the provisions of 3.6 of Annex 2:
 - a) when operated within class C airspace;
 - b) when forming part of aerodrome traffic at controlled aerodromes; or
 - c) when operated as special VFR flights.

7. An aircraft operated in accordance with the visual flight rules which wishes to change to compliance with the instrument flight rules shall:
 - a) if a flight plan was submitted, communicate the necessary changes to be effected to its current flight plan, or
 - b) when so required by 3.3 of Annex 2, submit a flight plan to the appropriate air traffic services unit and obtain a clearance prior to proceeding IFR when in controlled airspace.