

**VNSK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

Designation RWY NR	TRUE & MAG BRG	Dimensions of RWY (M)	Strength(PCN) and surface of RWY and SWY	THR Coordinates	THR elevation and Highest elevation of TDZ of Precision APP RWY
1	2	3	4	5	6
02		1255 × 30	Asphalt concrete		
20		1255 × 30	Asphalt concrete		
Slope of RWY-SWY					
7	8	9	10	11	12
.....	.....	.....	.....	.....	.....

**VNSK AD 2.13 DECLARED DISTANCES**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
02	1255	1255	1255	1255	
20	1255	1255	1255	1255	

**VNSK AD 2.14 APPROACH AND RUNWAY LIGHTING**

RWY Designator	APCH LGT type LEN INTST	THR LGT color WBAR	VASIS PAPI	TDZ LGT LEN	RWY Center Line LGT Length, spacing color, INTST	RWY edge LGT LEN, spacing color INTST	RWY End LGT color	SWY LGT LEN (M) color	Remarks
1	2	3	4	5	6	7	8	9	10
02			3.00 <sup>0</sup>						
20									

**VNSK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

1.	ABN Location, characteristics and hours of operation	
2.	LDI Location and LGT Anemometer Location and LGT	
3.	TWY edge and Centre line lighting	
4.	Secondary power supply / switch over time	
5.	Remarks	