

VNKT AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATION DATA

1.	Apron surface and strength	Surface - Cement Concrete Strength - PCN 53 R/B/W/T
2.	Taxiway width, surface and strength	Width - 23 m Surface - Bitumen Strength - PCN 54 F/A/W/T
3.	Altimeter check Point location and elevation	Location: - At Apron Elevation:-4394.76 ft
4.	VOR checkpoints	Ref VNKT AD 2-16
5.	INS checkpoints	Ref VNKT AD 2-14
6.	Remarks	-

VNKT AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1.	Use of aircraft stand ID signs, TWY guide lines and visual docking/ parking guidance system of aircraft stands	Taxiing guidance signs at all intersections with TWY and RWY and at all holding positions. Guide lines at apron. Nose-in guidance at aircraft stands
2.	RWY and TWY markings and LGT	RWY: RWY 02/20, THR, TDZ, Center line, RWY edge marked and RWY end THR, RWY edge have lights TWY: Center line, holding positions at all TWY/RWY intersections marked and edge with blue lights.
3.	Stop bars	Stop bars where appropriate.
4.	Remarks	-